



Model Name	System	09P	12P	15P	18P	24P
	Outdoor	ASH109PRDWA	ASH112PRDWA	ASH115PRDWA	ASH118PRDWA	ASH124PRDWA
	Indoor	ASYW09PRDWB	ASYW12PRDWB	ASYW15PRDWB	ASYW18PRDWB	ASYW24PRDWB
Cooling	Rated Capacity Btu/hr	9,000	12,000	15,000	17,000	22,000
	Capacity Range Btu/hr	3200-12500	3300-15000	5400-24000	5400-26500	6400-30000
	Rated Power Input W	620	960	1,200	1,360	1,760
	SEER	23.5	23.0	21.5	21.0	20.0
	EER	14.5	12.5	12.5	12.5	12.5
	Moisture Removal Pt./h	3.50	3.90	4.10	4.30	7.00
Heating	Rated Heating Capacity 47°F Btu/hr	10,000	13,000	16,000	22,000	27,600
	Heating Capacity Range Btu/hr	3800-15600	3900-20000	4000-26000	4000-30000	6200-36000
	Rated Power Input W	680	1,500	1,700	2,100	2,630
	HSPF	10.5	11.0	10.5	10.5	10.0
	Rated Heating Capacity 17°F Btu/hr	7,500	10,700	12,000	14,000	19,000
	Max. Heating Capacity 17°F Btu/hr	13,000	15,000	17,000	19,000	26,000
	Max. Heating Capacity 5°F Btu/hr	10,000	13,000	16,000	17,000	20,000
	Max Heating Capacity -4°F Btu/hr	8,500	10,000	12,000	14,000	15,000
	Max Heating Capacity -15°F Btu/hr	6,500	7,500	10,000	12,000	14,000
100% heating capacity @5F	Yes	Yes	Yes	No	No	
Operating Range	Cooling °F(°C)	14-115(-10-46)	14-115(-10-46)	14-115(-10-46)	14-115(-10-46)	14-115(-10-46)
	Heating °F(°C)	-15-75(-26-24)	-15-75(-26-24)	-15-75(-26-24)	-15-75(-26-24)	-15-75(-26-24)
Power Supply	Voltage, Cycle, Phase V/Hz/-	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Outdoor Unit	Compressor Type	DC inverter Driven Rotary				
	Maximum Fuse Size A	15	15	20	20	30
	Minimum Circuit Amp A	11.0	11.0	14.0	14.0	20.0
	Outdoor Noise Level dB	54	54	55	55	57
	Dimension: Height in (mm)	23 1/2 (597)	23 1/2 (597)	27 7/16 (697)	27 7/16 (697)	30 (762)
	Dimension: Width in (mm)	30 11/16 (780)	30 11/16 (780)	35 (890)	35 (890)	36 3/16 (920)
	Dimension: Depth in (mm)	11 7/16 (290)	11 7/16 (290)	13 7/8 (353)	13 7/8 (353)	15 1/8 (385)
ODU Weight (Ship/Net)- lbs	90.2/78.3	90.2/78.3	117.5/100.3	117.5/100.3	149.5/130.1	
Indoor Unit	Fan Speed Stages	5 + Auto	5 + Auto	5 + Auto	5 + Auto	5 + Auto
	Indoor Sound Level dB (Turbo/High/Med/Low/ Quiet)	44/40/35/31/23	45/41/36/32/23	48/46/42/36/34	48/46/42/36/34	49/47/42/36/34
	Dimension: Height in (mm)	12 1/4 (310)	12 1/4 (310)	13 1/4 (336)	13 1/4 (336)	13 1/4 (336)
	Dimension: Width in (mm)	35 7/16 (900)	35 7/16 (900)	43 7/8 (1115)	43 7/8 (1115)	43 7/8 (1115)
	Dimension: Depth in (mm)	8 7/16 (215)	8 7/16 (215)	9 9/16 (243)	9 9/16 (243)	9 9/16 (243)
	IDU Weight (Ship/Net)- lbs	30.9/25.4	30.9/25.4	43.2/35.3	43.2/35.3	45.4/37.5
Refrigerate Line	Connections	Flare	Flare	Flare	Flare	Flare
	Liquid O.D. in	1/4	1/4	1/4	1/4	1/4
	Suction O.D. in	3/8	3/8	1/2	1/2	1/2
	Factory Charge Oz	38.8	38.8	52.2	52.2	74.1
	Maximum Line Length Ft / m	50/15	50/15	83/25	83/25	83/25
	Maximum Height Ft / m	33/10	33/10	50/15	50/15	50/15

Operating Range (°F):



FEATURES & BENEFITS

OPTIONAL WIFI CONTROL



Remotely control ductless system from any smart phone or tablet



A-PAM DC INVERTER

Leading compressor technology for maximum comfort and efficiency




-15°F HEATING

Low ambient heating down to -15F (-26C)

BASE PAN HEATER



Prevents condensed water from freezing and blocking the base pan drain openings



3D AIR FLOW

Delivers air vertically and horizontally for even distribution throughout the room




BLUE FIN

A special coating that whisks away condensate water



LONG DISTANCE AIR SUPPLY

Optimized fan motor and blower design enables up to 60 feet of air flow



AUTO LOUVER

Automatically adjusts airflow upward when cooling, or downward when heating



WARM START

Ensures the fan will not blow cold air during heating mode startup



TURBO MODE

Cools or heats the room quickly



QUIET MODE

Minimizes indoor noise while maintaining comfort levels





Pub No. 66-X0059 09/13/19



Optional Accessories	Description
AWF01RWA	WiFi Module for Highwall Indoor
ACT17CWA	Easy Wired Controller
WK-B	Wired Controller Kit for Wall Mount Type Indoor

Our continuing commitment to quality products may mean a change in specifications without notice.



Compatible with Google Assistant and Amazon Alexa.



© 2020 GE Appliances, a Haier Company